G-Energy Cooling Buffer Tank

G-Energy Cooling is a buffer tank designed for cooling systems.

G-Energy Cooling can be used as a buffer tank for, e.g., water coolers and other mechanical cooling systems. Buffer tanks even out the conditions between the start-up times of cooling equipment and reduce the number of times compressors need to be started.

The G-Energy Cooling buffer tank is available as 501L, 1000L and 2000L models and in 3 or 6 bar pressure classes.

G-Energy Cooling is available with either a surface-treated steel or a stainless steel tank. The accumulator tanks are pressure-tested at the factory. A buffer tank has a 19mm cellular rubber insulation.

The steel base on the base of the accumulator makes hauling easier. The base on 501 and 1000 liter tanks has two parts; the lower section can be removed before installation. When lowered, the height of the 501 L accumulator tank is 90 mm, and the 1000 L accumulator tank 150 mm lower compared to the standard.

The accumulator has levelling feet with a 60 mm adjustment tolerance that makes it easy to set the accumulator to stand vertically



Tank connections and connection sizes

- 1. Charging/cooling, DN80/100
- 2. Venting, R1"
- 3. Drainage, R1"
- 4. Measurement, R1/2"

the lowermost in front R1" (3/4)



G-Energy Cooling Buffer Tank

| Model | | Cooling 501 3 BAR | Cooling 501 6 BAR | Cooling 1000 3 BAR | Cooling 1000 6 BAR | Cooling 2000 3 BAR | Cooling 2000 6 BAR |
|------------------------|-----|----------------------|----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| GTIN (64158) | | 52380714 | 52380721 | 52380738 | 52380745 | 52380752 | 52380769 |
| Tank capacity | L | 501 | 501 | 1000 | 1000 | 2000 | 2000 |
| Height | mm* | 2010 | 2010 | 2130 | 2130 | 2200 | 2200 |
| Height when lowered | mm* | 1920 | 1920 | 1980 | 1980 | | |
| Diameter | mm | 640 | 640 | 890 | 890 | 1240 | 1240 |
| Tilt measurement | mm | 2100 | 2100 | 2200 | 2200 | 2300 | 2300 |
| Weight | kg | 180 | 180 | 260 | 260 | 400 | 400 |
| Connection sizes #1 | DN | DN80 | DN80 | DN80 | DN80 | DN80 | DN80 |
| Material | | steel | steel | steel | steel | steel | steel |
| Max temperature | °C | 110 | 110 | 110 | 110 | 110 | 110 |
| Max operating pressure | bar | 3 | 6 | 3 | 6 | 3 | 6 |

^{* +}Levelling feet 0-60 mm

G-Energy Cooling RST Buffer Tank

| Model | | Cooling RST 501 3 BAR | Cooling RST 501 6 BAR | Cooling RST 1000 3 BAR | Cooling RST 1000 6 BAR | Cooling RST 2000 3 BAR | Cooling RST 2000 6 BAR |
|------------------------|-----|--------------------------|--------------------------|---------------------------|---------------------------|------------------------------|---------------------------|
| GTIN (64300) | | 79400441 | 79400458 | 79400465 | 79400472 | 79400489 | 79400496 |
| Tank capacity | L | 501 | 501 | 1000 | 1000 | 2000 | 2000 |
| Height | mm* | 2010 | 2010 | 2130 | 2130 | 2200 | 2200 |
| Height when lowered | mm* | 1920 | 1920 | 1980 | 1980 | | |
| Diameter | mm | 640 | 640 | 890 | 890 | 1240 | 1240 |
| Tilt measurement | mm | 2100 | 2100 | 2200 | 2200 | 2300 | 2300 |
| Weight | kg | 180 | 180 | 260 | 260 | 400 | 400 |
| Connection sizes #1 | DN | DN80 | DN80 | DN100 | DN100 | DN100 | DN100 |
| Material | | stainless steel | stainless steel | stainless steel | stainless steel | stainless steel | stainless steel |
| Max temperature | °C | 110 | 110 | 110 | 110 | 110 | 110 |
| Max operating pressure | bar | 3 | 6 | 3 | 6 | 3 | 6 |

^{* +}Levelling feet 0-60 mm